Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trad	le mark:	MAUL
-----------------	---------	----------	------

Supplier's address: Jakob Maul GmbH, Jakob-Maul-Str. 17, 64732 Bad König, DE

Model identifier: 8205209.200A

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

ing control

Lighting technol	logy used:	LED	Non-directional or directional:	NDLS
Light source cap	-type	Leiterplatten An-		
(or other electri	c interface)	schlussklemmen		
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product parar	neters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consummode (kWh/10 up to the neares	•	15	Energy efficiency class	D
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone errow cone (90º)	2 248 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode pow pressed in W	ver (P _{on}), ex-	15,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	540	Spectral power dis-	See image
sions without	Width	55	tribution in the	in last page
separate con- trol gear, light-	Depth	11	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	139	
		Chromaticity coordi-	0,311	
		nates (x and y)	0,336	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	colour rendering index value 4 Surviva		1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

