Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier'	S	name	or	trade	mark	: MAUL
-----------	---	------	----	-------	------	--------

Supplier's address: Jakob Maul GmbH, Jakob-Maul-Str. 17, 64732 Bad König, DE

Model identifier: 8205309.200A

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	Leiterplatten An-					
(or other electric interface)	schlussklemmen					
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Yes			
Product parameters						
Parameter	Value	Parameter	Value			

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	nption in on- 00 h), rounded st integer	11	Energy efficiency class	Е	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 430 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500	
On-mode pow pressed in W	ver (P _{on}), ex-	11,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82	
Outer dimen-	Height	400	Spectral power dis-	See image	
sions without	Width	50	tribution in the	in last page	
separate con- trol gear, light- ing control		6	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	95			
		Chromaticity coordi-	0,311			
		nates (x and y)	0,335			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

