## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	MAUL
--------------------------------	------

Supplier's address: Jakob Maul GmbH, Jakob-Maul-Str. 17, 64732 Bad König, DE

Model identifier: 8205609.200B

Tν	pe	of	light	source	•:
٠,	<b>P</b> C	٠.		504.00	••

Lighting technology used:	LED	Non-directional or	NDLS	
		directional:		
Light source cap-type	Leiterplatten An-			
(or other electric interface)	schlussklemmen			
Mains or non-mains:	NMLS	Connected light	No	
		source (CLS):		
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Product parameters				

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	mption in on- 00 h), rounded st integer	19	Energy efficiency class	E	
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	2 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500	
On-mode power (P <sub>on</sub> ), expressed in W		18,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	83	
Outer dimen-	Height	540	Spectral power dis-	See image	
sions without	Width	55	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	5	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	157	
		Chromaticity coordi-	0,312	
		nates (x and y)	0,335	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	6	Survival factor	1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

